



CAT6-CMP

Description

23 AWG Plenum, unshielded four twisted pairs, Category 6 Cable. Extended testing to 550 MHz.

Description

CMP Rating Verified to ANSI/TIA/EIA 568C.2 Category 6, RoHS Compliant

Applications

Supports all Gigabit Ethernet/1000BASE-T/IEEE 802.3ab, ATM up to 155 Mbps, 100 Mbps Fast Ethernet 100BASE-T/IEEE 802.3, ANSI.X3.263 FDDI TP-PMD, Ethernet 10BASE-T/IEEE 802.3, 4 & 16 Mbps Token Ring/IEEE 802.5, T1/E1, xDSL, ISDN, 550 MHz Broadband Video and standards under development such as ATM at 622 Mbps, 1.2, 2.4 and 4.8 Gbps

Construction

Conductor: 23 AWG Solid Bare Copper
Number of Pairs: 4 Pair
Jacket Material: Flame Retardant Polyvinyl Chloride
Nominal Overall Cable Diameter: 0.240 in.
Approximate Cable Weight: 34 lb/1,000 ft.

Packaging

EZ-Pull Box (KINK-FREE Technology)

Available Colors



ELECTRICAL & PHYSICAL PROPERTIES

Temperature Rating:	Installation: 0°C to 50°C Operation: -2°C to 60°C
Velocity of Propagation:	72%
Mutual Capacitance:	14 pF/ft Nominal
Capacitance Unbalance:	330 pF/ft maximum
Maximum Conductor D.C.R.:	28.6 Ω /1,000 ft
Maximum D.C.R. Unbalance:	3%
Maximum Delay Skew:	18 ns/100m
Characteristic Impedance:	
	From 0.772 MHz - 100 MHz 100 ± 15%
	From 100 MHz - 250 MHz 100 ± 22%
	From 251 MHz - 550 MHz 100 ± 32%
Minimum bend radius:	1.0 in.

PHONE: (301) 836-1195

2 Wisconsin Circle,
Suite 700 Chevy Chase,
MD 20815

sales@tscables.com

The information provided here in is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.